

Selectable Gallonage Monitor Nozzle



PT. SKOTFIRE & SAFETY TECHNOLOGY
 Komp. Ruko Vila Nusa Indah II Blok W3 No. 16
 Bojongsukur - Gunung Putri 16969 - INDONESIA
 Phone: +62 21 82401515
 e-mail: skotfire@skotfire.com

BALIKPAPAN BRANCH OFFICE
 Jl. Kol. Syarifuddin Yoes, Ruko Central Bizpark 2,
 Blok HRM No 02, Balikpapan Selatan - 76114

SkotFire
 AND SAFETY TECHNOLOGY

Style 846-BC

- 250-400-550-750 GPM (950-1600-2000-2900 LPM)
- Optional 500-1000-1500-2000 LPM
- Corrosion resistant brass construction
- Combination pattern, master stream nozzle with four distinct, calibrated and selectable flow settings
- Combination of straight stream and variable fog patterns
- Selectable flow rate, changeable even during flowing conditions
- Reduces the risk of injury from manually changing tips on deck
- Spinning teeth produce dense, wide, fully adjustable fog pattern
- Heavy-duty protective rubber bumper
- Low maintenance components
- Compatible with Protek's wide range of monitors



Specification

Style	Material	Inlet Size	Flow @ 100 psi (7 bar)		Teeth	Length	Weight
			GPM	LPM			
846-BC	Brass	2-1/2" (65mm)	250-400-550-750	500-1000-1500-2000*	Spinning	8.3" (211mm)	16 (7.3)

*Flow setting of 950-1600-2000-2900 LPM is available on request